

AJE-PAWANA



Product colour	Black
Bulb lifetime	30000 h
Product colour	White
AC input voltage	220-240 V
Color Rendering Index (CRI)	80
Suitable location	Hallway
Suitable for indoor use	Yes
Power source type	AC
Height	200 mm
Suitable location	Home office
Suitable location	Office
Suitable location	Bathroom
Light colour	Neutral white
Suitable for outdoor use	No
Mounting type	Surfaced
Glass colour	White
Bulb power	20 W
Quantity per pack	1 pc(s)
Housing material	Metal
Housing material	Plastic
Suitable location	Universal
Lighting style	Classical
Suitable location	Bedroom
Rotating	No
	No
Suitable location	Restaurant
Suitable location	Restaurant
Suitable location Dimmer	Restaurant No
Suitable location Dimmer Width	Restaurant No 600 mm
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min)	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 Im
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 lm Yes
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 Im Yes 130 mm
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 Im Yes 130 mm No
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 Im Yes 130 mm No
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type Package depth	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 lm Yes 130 mm No LED 225 mm
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type Package depth Suitable location	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 Im Yes 130 mm No LED 225 mm Corridor
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type Package depth Suitable location Suitable location	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 lm Yes 130 mm No LED 225 mm Corridor Dining room
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type Package depth Suitable location Suitable location Package height	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 Im Yes 130 mm No LED 225 mm Corridor Dining room 90 mm
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type Package depth Suitable location Suitable location Package height Additional information	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 lm Yes 130 mm No LED 225 mm Corridor Dining room 90 mm The light source cannot be replaced
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type Package depth Suitable location Suitable location Package height Additional information Fitting/cap type	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 Im Yes 130 mm No LED 225 mm Corridor Dining room 90 mm The light source cannot be replaced Non-changeable bulb(s)
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type Package depth Suitable location Suitable location Package height Additional information Fitting/cap type Sustainability compliance	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 Im Yes 130 mm No LED 225 mm Corridor Dining room 90 mm The light source cannot be replaced Non-changeable bulb(s) Yes
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type Package depth Suitable location Suitable location Package height Additional information Fitting/cap type Sustainability compliance Additional information	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 Im Yes 130 mm No LED 225 mm Corridor Dining room 90 mm The light source cannot be replaced Non-changeable bulb(s) Yes The lamp contains built-in LEDs
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type Package depth Suitable location Suitable location Suitable location Package height Additional information Fitting/cap type Sustainability compliance Additional information Number of bulbs	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 lm Yes 130 mm No LED 225 mm Corridor Dining room 90 mm The light source cannot be replaced Non-changeable bulb(s) Yes The lamp contains built-in LEDs 50 bulb(s)
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type Package depth Suitable location Suitable location Package height Additional information Fitting/cap type Sustainability compliance Additional information Number of bulbs Package width	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 lm Yes 130 mm No LED 225 mm Corridor Dining room 90 mm The light source cannot be replaced Non-changeable bulb(s) Yes The lamp contains built-in LEDs 50 bulb(s) 605 mm
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type Package depth Suitable location Suitable location Package height Additional information Fitting/cap type Sustainability compliance Additional information Number of bulbs Package width Energy efficiency class	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 Im Yes 130 mm No LED 225 mm Corridor Dining room 90 mm The light source cannot be replaced Non-changeable bulb(s) Yes The lamp contains built-in LEDs 50 bulb(s) 605 mm G
Suitable location Dimmer Width Tiltable head (up-down) Certification Colour temperature (min) International Protection (IP) code Luminous flux Adjustable spot head Depth On/off switch Bulb type Package depth Suitable location Suitable location Package height Additional information Fitting/cap type Sustainability compliance Additional information Number of bulbs Package width	Restaurant No 600 mm Yes CE, RoHS, ISO 9001, ISO 14001 4000 K IP44 1200 lm Yes 130 mm No LED 225 mm Corridor Dining room 90 mm The light source cannot be replaced Non-changeable bulb(s) Yes The lamp contains built-in LEDs 50 bulb(s) 605 mm

Energy consumption per 1000 hours	12 kWh
Input voltage	220-240 V
Compliance certificates	RoHS
Compliance certificates	CE
EAN	5901443113638